

SPECKTRON

DKS1-65AD

65" Double Sided Kiosk



- Double sided 4K display
- Freestanding slim line design
- Protective glass fascia & built-in speakers
- 65" double sided
- Integrated Android system
- Supports superior video content & applications



4K
ULTRAHD

ULTRA
HD



SLIM

SLEEK
DESIGN



USB
CONNECTIVITY

USB
CONNECTIVITY



RETAIL



LEISURE



HOSPITALITY



HEALTHCARE



GOVERNMENT



MALLS



AIRPORTS

DKS1-65AD



Specktron's 65" Double Sided Digital Kiosk is the ideal solution for a variety of environments, such as hospitality, retail, airports & public spaces. Featuring Ultra HD resolution, 178°/178° wide-angle viewing, 400 cd/m² brightness, 24/7 operation, vivid clarity in a sleek, slim design. Photo and video files can be played back using the Quad-core media player and 8GB of internal memory.

SPECIFICATIONS

PANEL		ANDROID SYSTEM	
Panel Size	65"	Operating system	Android 6.0.1
Max-Resolution(H*W)	2160*3840	CPU	Quad Core, Cortex A-17
Viewing angle	178°	Memory	2 GB DDR3 RAM
Display colors	16.7 million	Storage	8 GB
Brightness	400 cd/m ²	Internet connection	Wi-Fi and LAN
Contrast ratio	1500:1	SD Card Support	Yes (up to 32 GB)
Response time	8ms	Google Play Support	Yes
Display model	9-16	Scheduled On/ Off power	Yes
24/7 Operation	Yes	Inputs	HDMI-IN*2, USB ports*2, RJ 45*1
Speakers	2 x 5W	Outputs	HDMI-OUT*1
SUPPORTING FORMATS		CMS	Supports pushing content and remote management of unit
Video format	AVI(H.264, DIVX, DIVXVIDEO), rm, rmvb, MKV(H.264, DIVX, DIVXVIDEO), WMV, MOV, MP4(H.264, MPEG, DIVX, XVID), DAT(VCD format), VOB(DVD format), PMP, MPEG, MPG, FLV(H.263, H.264), ASF, TS, TP, 3GP, MPG	CARTON DIMENSIONS	
Audio format	MP3, WMA, MP2, OGG, AAC, M4A, M4A4, FLAC, APE, 3GP, WAV.	Dimensions and weight	2358 x 1178 x 345 (188 kgs)
Picture format	BMP/ PNG/ GIF/ JPEG	CERTIFICATIONS	
Text format	PDF, WORD, PPT, TXT, EXCEL	CE	Yes
POWER		ROHS	Yes
Power Supply	AC 100~240V 50 /60 HZ	PRODUCT DIMENSIONS	
Power Consumption	250W	Dimensions	2200 x 1001 x 187.5, Base 600 x 1007 x 100
Standby	<5W	Weight	166 kgs
		Operating temperature	-10°C~55°C
		Operating humidity	10%-90%
		Storage temperature	-20°C~60°C
		Storage humidity	10%-90%

*Model subject to availability in your region.